

# SELECTOR SWITCHES

## XHS: Selector Switch Operators

### FEATURES

- Die cast aluminum alloy. The barrels are all 3/4" NPSM thread. Maximum installation thickness: 1 15/16" long barrel, 3/4" short barrel.
- Specify 2 position or 3 position. For 3-position, order must specify cam (see contact block page for contact sequence chart).
- All operators have black molded nylon knobs. The exposed metal parts are black anodized aluminum. Metal caps are also available in blue, gold, clear, red or green with black knobs. Specify colors required.
- Contact blocks are not included with XHSS operators. Select contact block and sequence operating cam from contact block page. (See accessories at end of section)

### LONG BARREL

Catalog #	Cam	# Pos.	Operator Description	Weight (lbs.)
XHSS		2/3	Long Barrel	1/2
XHSC*		3	Spring Return to Center from Right and Left	1/2
XHSR2	2	2	Spring Return to Left from Right	1/2
XHSR		3	Spring Return to Center from Right, Maintain Left	1/2
XHSL2	4	2	Spring Return to Right from Left	1/2
XHSL		3	Spring Return to Center from Left, Maintain Right	1/2

### SHORT BARREL

Catalog #	Cam	# Pos.	Operator Description	Weight (lbs.)
XHSSS		2/3	Short Barrel	1/2
XHSSC*		3	Spring Return to Center from Right and Left	1/2
XHSSR2	2	2	Spring Return to Left from Right	1/2
XHSSR		3	Spring Return to Center from Right, Maintain Left	1/2
XHSSL2	4	2	Spring Return to Right from Left	1/2
XHSSL		3	Spring Return to Center from Left, Maintain Right	1/2

\*3 Position Only

### SELECTOR SWITCH


Catalog #	Operator Description	Weight (lbs.)
XHSSPL	w/padlock device Long Barrel	3/4
XHSSSPL	w/padlock device Short Barrel	3/4

### LEGEND PLATES AT END OF SECTION

**NOTE** For extremely wet-dirty location applications, use protective boots.  
EXCLUDES PADLOCK DEVICES.

### Certifications

Class I, Division 1, Groups B, C & D  
Class II, Groups E, F & G  
NEMA 7 & 9 / NEMA 4 / IP66



XHSS Series



XHSSS Series



XHSSPL



XHSSSPL